



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SolAero Sprühkleber (71003)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

1.3. Details of the supplier of the safety data sheet

Company name:	Friedrich Huber aeronova GmbH & Co.	
Street:	Sobrigauer Weg 4	
Place:	D-01257 Dresden	
Telephone:	0049-(0)351-27046-0	Telefax: 0049-(0)351-2704616
E-mail:	info@aeronova.de	
Contact person:	Labor	Telephone: 0049-(0)351-2704615
E-mail:	labor@aeronova.de	
Internet:	www.aeronova.de	

1.4. Emergency telephone number: 0049-(0)351-27046-0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229
Skin Irrit. 2; H315
STOT SE 3; H336
Asp. Tox. 1; H304
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Hydrocarbons, C6, isoalkanes, <5% n-hexane

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 2 of 13

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to in accordance with local/regional/national/international regulation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No Index No REACH No	
	Classification (Regulation (EC) No 1272/2008)	
115-10-6	dimethyl ether	70 - < 75 %
	204-065-8 603-019-00-8 01-2119472128-37	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280	
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	10 - < 12.5 %
	927-510-4 01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411 EUH066	
	Hydrocarbons, C6, isoalkanes, <5% n-hexane	5 - < 10 %
	931-254-9 01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
110-54-3	n-Hexane	0,1 - < 1 %
	203-777-6 601-037-00-0 01-2119480412-44	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H372 H304 H411	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
115-10-6	204-065-8	dimethyl ether	70 - < 75 %
		inhalation: LC50 = 164000 ppm (gases)	
64742-49-0	927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	10 - < 12.5 %
		oral: LD50 = >5840 mg/kg	
	931-254-9	Hydrocarbons, C6, isoalkanes, <5% n-hexane	5 - < 10 %
		inhalation: LC50 = > 20 mg/l (vapours); oral: LD50 = >5000 mg/kg	

Further Information

n-hexane is a component of the hydrocarbon

SECTION 4: First aid measures

4.1. Description of first aid measures



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 3 of 13

General information

When in doubt or if symptoms are observed, get medical advice.
If medical advice is needed, have product container or label at hand.

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Headache, Dizziness, Impaired consciousness
Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Do not breathe gas/vapour/aerosol.

For non-emergency personnel

Ventilate affected area. Remove persons to safety. Do not breathe gas/vapour/aerosol.

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 4 of 13

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Do not breathe gas/vapour/aerosol. Use only outdoors or in a well-ventilated area.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Adhesives, sealants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
115-10-6	Dimethylether	1000	1920		TWA (8 h)	
110-54-3	n-Hexane	20	72		TWA (8 h)	



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 5 of 13

DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
115-10-6	dimethyl ether		
Consumer DNEL, long-term	inhalation	systemic	471 mg/m ³
Worker DNEL, long-term	inhalation	systemic	1894 mg/m ³
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
Worker DNEL, long-term	dermal	systemic	300 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	2085 mg/m ³
Consumer DNEL, long-term	dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	447 mg/m ³
Consumer DNEL, long-term	oral	systemic	149 mg/kg bw/day
	Hydrocarbons, C6, isoalkanes, <5% n-hexane		
Worker DNEL, long-term	inhalation	systemic	5306 mg/m ³
Worker DNEL, long-term	dermal	systemic	13964 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	1131 mg/m ³
Consumer DNEL, long-term	dermal	systemic	1377 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	1301 mg/kg bw/day
110-54-3	n-Hexane		
Worker DNEL, long-term	inhalation	systemic	75 mg/m ³
Worker DNEL, long-term	dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	16 mg/m ³
Consumer DNEL, long-term	dermal	systemic	5,3 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	4 mg/kg bw/day

PNEC values

CAS No	Name of agent	
Environmental compartment	Value	
115-10-6	dimethyl ether	
Freshwater	0,155 mg/l	
Freshwater (intermittent releases)	1,549 mg/l	
Marine water	0,016 mg/l	
Freshwater sediment	0,681 mg/kg	
Marine sediment	0,069 mg/kg	
Microorganisms in sewage treatment plants (STP)	160 mg/l	
Soil	0,045 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Do not breathe gas/vapour/aerosol. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection. Suitable eye protection: Eye glasses with side protection EN ISO 16321



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 6 of 13

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Recommended material: NBR (Nitrile rubber) EN ISO 374

Thickness of the glove material: 0,4 mm

Breakthrough time: >=480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Suitable respiratory protection apparatus:
Combination filtering device A-P2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	light beige
Odour:	like: Solvent

Melting point/freezing point:	not applicable
Boiling point or initial boiling point and boiling range:	< -20 °C
Flammability:	not determined
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	26,2 vol. %
Flash point:	< -20 °C
Auto-ignition temperature:	200 °C
Decomposition temperature:	not determined
pH-Value:	not applicable
Viscosity / kinematic:	not determined
Water solubility: (at 20 °C)	practically insoluble
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0,7 g/cm ³ calculated.
Relative vapour density:	not determined
Particle characteristics:	not applicable

Test method

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Heating may cause an explosion.

Sustained combustibility:

No data available

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 7 of 13

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: May burst if heated.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
115-10-6	dimethyl ether				
	inhalation (4 h) gas	LC50 164000 ppm	Rat	REACH Registration Dossier	OECD Guideline 403
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics				
	oral	LD50 >5840 mg/kg	Rat	Study report (1961)	OECD Guideline 401
	Hydrocarbons, C6, isoalkanes, <5% n-hexane				
	oral	LD50 >5000 mg/kg	Rat	Pre-supplier/manufacturer	OECD 401
	inhalation (4 h) vapour	LC50 > 20 mg/l	Rat	Pre-supplier/manufacturer	OECD 403

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 8 of 13

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Hydrocarbons, C6, isoalkanes, <5% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

Based on available data, the classification criteria are not met.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
115-10-6	dimethyl ether					
	Acute fish toxicity	LC50 > 4100 mg/l	96 h	Poecilia reticulata	REACH Registration Dossier	other: NEN 6504 Water - Determination of
	Acute algae toxicity	ErC50 154,917 mg/l	96 h	green algae	REACH Registration Dossier	other: Data generated using ECOSAR v1.00
	Acute crustacea toxicity	EC50 > 4400 mg/l	48 h		REACH Registration Dossier	other: NEN6501: Water -Determination of
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics					
	Acute fish toxicity	LL50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 7,4 mg/l	48 h		SIDS Initial Assessment Report For SIAM	OECD Guideline 202
	Crustacea toxicity	NOEC 1 mg/l	21 d		REACH Registration Dossier	OECD Guideline 211
	Hydrocarbons, C6, isoalkanes, <5% n-hexane					
	Acute fish toxicity	LC50 18,3 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Pre-supplier/manu facturer	
	Acute algae toxicity	ErC50 13,6 mg/l	72 h	Pseudokirchneriella subcapitata	Pre-supplier/manu facturer	
	Acute crustacea toxicity	EC50 3,87 mg/l	48 h		Pre-supplier/manu facturer	
110-54-3	n-Hexane					
	Acute fish toxicity	LC50 2,5 mg/l	96 h	Pimephales promelas	Geiger et al. 1990	

12.2. Persistence and degradability



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 9 of 13

The product has not been tested.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics				
	Biodegradation	81%		28	
	Readily biodegradable (according to OECD criteria).				
	Hydrocarbons, C6, isoalkanes, <5% n-hexane				
	OECD 301F	98 %		28	
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,07
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	>= 3,07
	Hydrocarbons, C6, isoalkanes, <5% n-hexane	3,6
110-54-3	n-Hexane	3,9

BCF

CAS No	Chemical name	BCF	Species	Source
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	>= 95,35		REACH Registration D

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Based on available data, the classification criteria are not met.

12.6. Endocrine disrupting properties

Based on available data, the classification criteria are not met.

12.7. Other adverse effects

No further relevant information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 10 of 13

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63 190 277 327 344 381 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1





SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 11 of 13

Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
n-Hexane

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: 89,447 % (626,126 g/l)

Directive 2004/42/EC on VOC in paints and varnishes: 89,447 % (626,126 g/l)

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC, 2008/47/EC
Aerosol Directive (75/324/EEC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

dimethyl ether
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Hydrocarbons, C6, isoalkanes, <5% n-hexane
n-Hexane

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,11,12,14,15,16.



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 12 of 13

Abbreviations and acronyms

Flam. Gas 1: Flammable gases, hazard category 1
Aerosol 1: Aerosols, hazard category 1
Press. Gas (Liq.): Gases under pressure: Liquefied gas
Flam. Liq. 2: Flammable liquids, hazard category 2
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Irrit. 2: Skin irritation, hazard category 2
Repr. 2: Reproductive toxicity, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
STOT RE 1: Specific target organ toxicity - repeated exposure, hazard category 1
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
assessment, chapter R.20 (Table of terms and abbreviations).
EC/EEC: European Community/European Economic Community
EU: European Union
M-factor: Multiplying factor
IATA: International Air Transport Association
DGR: Dangerous Goods Regulations



SolAero Sprühkleber (71003)

Revision: 26.05.2026

Page 13 of 13

ICAO: International Civil Aviation Organization

TI: Technical Instructions

VOC: volatile organic compound

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)